

SAFETY DATA SHEET

1 of 7 Fuzion NanoFlex

Prepared to OSHA, ANSI, NOHSC, WHMIS, 1002/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 6/22/17

	1. PRODUCT INDENTIFICATION			
1.1	Product Name:			
	Fuzion NanoFlex			
1.2	Chemical Name:			
	POLYURETHANE (METH)ACRYLATE PREPOLYMER RESIN BLEND			
1.3	Synonyms:			
	NA NA			
1.4	Trade Names:			
	NA NA			
1.5	Product Use:			
	PROFESSIONAL USE ONLY			
1.6	Manufacturer's Name:			
	FUZION GEL LTD.			
1.7	Manufacturer's Address:			
	104-2631 ENTERPRISE WAY, KELOWNA, BRITISH COLUMBIA, CANADA			
1.8	Emergency Phone:			
	CHEMTREC: +1 703 527 3887 / +1 800 424 9300 (CCN 696869)			
1.9	Business Phone / Fax:			

2. HAZARD INDENTIFICATION

2.1 Hazard Identification:

+1 -844-748-9324

WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. CAUSES EYE IRRITATION. Hazard Statements (H):H317 - May cause an allergic skin reaction. H320 - Causes eye irritation. Precautionary Statements (P): P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Containinated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rince continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - ilf eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 - Wash contaminated clothing before resuse. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



2.2 Routes of Entry: Inhalation: YES Absorption: YES Ingestion: YES

2.3 Effects of Exposure:

INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervouse system depression.

EYES & SKIN: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye

inflamation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to the skin, especially after prolonged contact. The product can cause allergic skin

reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated expsoure.

INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system.

Symptoms of overexposure can include coughing, wheezing, nasal congestion and difficulty breathing. Inhalation of concentrated vaors can cause central nervous system depression (e.g., drowsiness, headaches, nausea). Odor may give

some warning of exposure but odor fatigue may occur.

2.4 Symptoms of Overexposure:

Symptoms of skin overexposure may include redness, itiching and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, deratitis) upon prolonged or repeated exposure.

2.5 Acute Health Effects:

Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and

2.6 Chronic Health Effects:

The material may cause an allergic reaction for some sensitive individuals.

2.7 Target Organs:

Eyes, skin

		3. COMP	OSITION 8	& INGRE	DIENT	INFC	DRMA	OITA	N				2 of 7
					EXPC	SURE I	LIMITS	IN AIR	(mg/m	13)			
					AC	GIH		NOHS	С		OSHA	1	
					р	pm		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
Bis-HEA Poly(1,4-	NA	NA	NA	20-60	NA	NA	NA	NF	NF	NA	NA	NE	
butanediol)-9 / IPDI													
Copolymer													
51 115111	22222 4 2 2	I	Tara	Tan an	1	1	T	T	T	1	1	I	
Bis-HEMA	82339-16-0	NA	NA	20-60	NA	NA	NF	NF	NF	NA	NA	NA	
Polyneopentyl Glycol													
Adipate/ IPDI													
Copolymer Trimethylpropane	3290-92-4	NA	NA	5-20	NA	NA	NF	NF	NF	NA	NA	NA	
trimethacrylate	3230-32-4	INA	INA	3-20	IVA	INA	141	INI	INI	IVA	INA	IVA	
Tripropyleneglycol	42978-66-5	NA	NA	5-20	NA	NA	NF	NF	NF	NA	NA	NA	
diacrylate	12070 00 0		1	0 20	1		1	1	1	1	1		
1-Hydroxylcyclohexyl	947-19-3	NA	213-426-9	0.1 - 5	NA	NA	NF	NF	NF	NA	NA	NA	
phenyl ketone			<u> </u>										
Benzophenone	116-61-9	NA	204-337-6	0.1 - 5	NA	NA	NF	NF	NF	NA	NA	NA	
	Aquatic chromic	c 2; Aquatic acu	ite 1; H411, H	400									
bis-trimethylbenzoyl	162-881-26-7	NA	423-340-5	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA	
phenyl phosphine	Skin Sens. 1; Aq	uatic Chronic 4	; H317, H413										
MAY ALSO CONTAIN	l:												
CI 77891 (Titanium	13463-67-7	XR2275000	236-675-5	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA	
Dioxide)		•	_	1				•					
CI 15850 (Red 6)	17852-98-1	NA	241-806-4	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
					_		1	_		1			
Calcium Sodium	65997-17-3	NA	N266-17-3	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
Borosilicate		1	T	T	T	1	1	T	T	T	1	I I	
Silver	7440-22-4	231-131-3	215-168-2	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
C177400 (In an Ontide a)	12227 00 2	Lara	245 277 5	10.1	Tara	1	NIE	NE	NE	LNIA	I N I A	INA I	
CI77499 (Iron Oxides)	12227-89-3	NA	215-277-5	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
			4. FIRST	L AID M	IEASI	JRFS	<u> </u>						
4.1 First Aid:				. ,	, 10 (
INGESTION:	If ingested, do i	not induse ve	itinal If arad	ict has bee	ח בעים וו	wed .	drink =	lonty -	of wata	r or	ilk inan	MEDIATE	IV If tha
INGESTION:	patient is vomit						•	-					
	•	Center or local			_						•		

the amount of the substance that was swallowed. SKIN & EYES: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water followed by a thorough washing of the affected area with plenty of soak and waster. Remove all contaminated clothing including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately. INHALATION: Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention. HEALTH 4.2 Medical Conditions Aggravated by Exposure: 1 Pre-existing dermatitis, other skin conditions and disorders of the target organs (eyes, skin) **FLAMMABILITY** 0 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В EYES SKIN

5. FIREFIGHTING MEASURES 3 of 7 5.1 Flashpoint & Method: > 100 °C (> 212 °F) 5.2 Autoignition Temperature: NA 5.3 Flammability Limits: Lower Explosive Limit (LEL): NA Upper Explosive Limit (UEL): NA 5.4 Fire & Explosion Hazards: When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox) 5.5 Extinguishing Methods: Water, Foam, CO2, Dry Chemical 5.6 Fire Fighting Procedures: First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water before returnign to service.

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., , 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entery to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING AND STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

7.3 Special Precautions:

Do not store where temperatures can exceed 50 $^{\circ}$ C (122 $^{\circ}$).

	8. EX	(POSURE CONTROLS & PERSONAL PROTECTION	4 of 7	
8.1	8.1 Ventilation & Engineering Controls: Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decontainmentation equipment is available (e.g., sink, safety shower, eye wash station).			
8.2	Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia.		
8.3	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.		
8.4	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or imprevious gloves.		
8.5	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.		

	9. PHYSICAL & CHEMICAL PROPERTIES					
9.1	Density:	1.1				
9.2	Boiling Point:	NA				
9.3	Melting Point:	ND				
9.4	Evaporation Rate:	NA				
9.5	Vapor Pressure:	ND				
9.6	Molecular Weight:	NE				
9.7	Appearance & Color:	Clear or pigmented liquid				
9.8	Odor Threashold:	NE				
9.9	Solubility:	Not soluble				
9.1	pH:	NA				
9.1	Viscosity:	approximately 65,000 cps				
9.1	Other Information:	NA				

	10. STABILITY & REACTIVITY				
10	Stability:				
	Relatively stable under ambient conditions when stored properly.				
10	Hazardous Decomposition Products:				
	If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of				
	carbon and nitrogen).				
10	Hazardous Polymerization:				
	Will not occur.				
10	Conditions to Avoid:				
	Exposure or contact to extreme temperatures, incompatable chemicals, strong light sources, sparks and flame.				
11	Incompatable Substances:				
	Strong oxidizers, peroxides, strong acids or alkalis.				

	11. TOXICOLOGICAL INFORMATION 5 of 7
11	Toxicity Data:
	This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the produ t which
	are found in scientific literature. These data have not been presented in this document.
11	Acute Toxicity:
	See Section 2.5
11	Chronic Toxicity:
	See Section 2.6
11	Suspected Carcinogen:
	The ingredients of this product are not listed as carcinogens by the National Toxicology Program and have not been evaluated by the Internail
	Agency for Research on Cancer or the American Conference of Government Industrial Hygenists.
12	Reproductive Toxicity:
	This product is not reported to cause reproductive toxicity in humans.
	Mutagenicity:
	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:
	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:
	This products is not reported to cause teratogenic effects in humans.
12	Irritancy of Product:
	See Section 2.3
12	Biological Exposure Indicies:
	NE
12	Physician Recommendations:
	Treat syptomatically
	12. ECOLOGICAL INFORMATION
12	
12	Environmental Stability:
12	This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Effects on Plants & Animals:
12	
12	There is no specific data availble for this product on plant life. Effects on Aquatic Life:
12	There is no specific data availble for this product on aquatic life.
	There is no specific data available for this product on aquatic file.
	13. DISPOSAL CONSIDERATIONS
13	Waste Disposal:
12	Dispose inaccordance with local, state and Federal waste laws.
13	Special Considerations: This material becomes an input pleatic upon prelanged synapsys to source of LIV light and synlight. Dispect of input pleatics is refer for the
	This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the
	environment and is more easily handled for disposal according to local, state and Federal regulations.
	14. TRANSPORTATION INFORMATION
The b	asic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation.
	ional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADR and the CTDGR.
	49 CFR (GRD):
	NOT REGULATED
14	IATA (AIR):
	NOT REGULATED
14	IMDG (OCN):
	NOT REGULATED
14	TDGR (Canadian GND):
	NOT REGULATED
4.5	ADR/RID (EU):
15	
15	
	NOT REGULATED
	NOT REGULATED MEXICO (SCT):
15	NOT REGULATED

17

Prepared by: Fuzion Gel LTD.

Kelowna, BC Tel: 1-844-748-9324 www.nailfuzion.com

104-2631 Enterprise Way

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH American Conference on Governmental Industrial Hygienists			
TLV Threshold Limit Value			
OSHA U.S. Occupational Safety and Health Administration			
PEL Permissible Exposure Limit			
IDLH Immediately Dangerous to Life and Health			

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	
1 Slight Hazard		
2	Moderate Hazard	
3	Severe Hazard	
4	4 Extreme Hazard	



PERSONAL PROTECTION RATINGS:

Α		
В		
С		
D		
Е		
F		





Splash Goggles









Synthetic Apron

Protective Clothing & Full Suit

Dust Respirator





Full Face Respirator Mask Respirator

Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available	
NR	NR No Results	
NE	Not Established	
ND	ND Not Determined	
ML	ML Maximum Limit	
SCBA	Self-Contained Breathing Apparatus	

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals			
	S			
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal			
ppm	Concentration expressed in parts of material per million parts			
TD _{Io}	Lowest dose to cause a symptom			
TCLo	Lowest concentration to cause a symptom			
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects			
TC, TC _o , LC _{io} , & LC _o				
IARC	International Agency for Research on Cancer			
NTP	National Toxicology Program			
RTECS	Registry of Toxic Effects of Chemical Substances			
BCF	Bioconcentration Factor			
TL _m	Median threshold limit			
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution			

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	((a)	②	①	®		Ŕ
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		*	*		9	X	X
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

		®				(!)		(
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment